POWERMATIC®

Installation Instructions 701-RB Riser Block Kit

For use with the Powermatic 701 Mortiser

Shipping Contents Description

Stock No

701-RB Riser Block Kit 1791312

Kit includes:

1 ea ...2-inch Riser Block

4 ea ... Socket Head Cap Screw (M8 x 80)

Tools Required for Assembly

6mm Hex Wrench

Installation Instructions

- Disconnect the mortiser from the power source.
- 2. Remove the fence (H).
- 3. Remove the four socket head cap screws, lock washers and flat washers that hold the *mortiser* (A) to the *base* (F).
 - Save the *lock washers* (C) and *flat washers* (D). They will be reused in Step 5
- 4. Move the *mortiser* (A) to the side and place the *riser block* (G) on the *base* (F).
- Use the new socket head cap screws (B) provided with the riser block kit, lock washers (C) and flat washers (D) (from Step 3) to attach the mortiser (A) to the riser block (G) and base (F).
- 6. Reattach the fence (H) by sliding the rack (J) into the slot in the *riser block* (G).

Note: The fence *adjust knob* (E) is no longer functional. Fence adjustment is accomplished by loosening the lock handles and sliding the fence to the desired position.



427 New Sanford Road LaVergne, Tennessee 37086 Ph.: 800-274-6848 www.powermatic.com